## NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:



 $\sum$  CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off

NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:

All so

CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off

NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:



CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off

NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:

- Alino



NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:



CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off

NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:



 $\Delta$  CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off

NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:





NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:





NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:





CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off

NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:





NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:





CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off

NOTE: If the cartridge does not snap into place, remove the cartridge from the carriage.

Gently bend the tab away from the cartridge, and then reinsert the cartridge into the

carriage. Bend the tab away from the cartridge:





CAUTION: Be careful not to bend the tab out more than 1.27 cm (0.5 inches). Moving the tab too far might damage the cartridge or cause the tab to break off